



Simplified Menu Start Up Instructions

TP500S Control Panels



Display Icons




- | | | |
|-----------------------------|-------------------|---------------------------------------|
| A - Heat | F - Light | K - Auxiliary (Jets 3 or MICRO SILK™) |
| B - Ready Mode | G - Cleanup Cycle | L - Temperature Range (High / Low) |
| C - Rest Mode | H - Jets 1 | M - Set (Programming) |
| D - bba™2 On | I - Jets 2 | N - Filter Cycle (1 or 2 or Both) |
| E - WiFi (Cloud Connection) | J - Blower | |



EASY START UP

- Connect Hot Tub to Power
- Allow Pumps to Prime
- Set Temperature
- Set Filter Cycle

Priming Mode



Your spa will enter Priming Mode when it is connected to power. During Priming Mode ([RUN][PMPS][PURG][AIR]), press “Jet 1” and “Jet 2” button twice to turn pumps on high-speed, to ensure pumps are free of air. Priming Mode lasts 4-5 minutes or you can exit the Priming Mode by pressing “Warm” and “Cool” at the same time.

Note: Exiting Priming Mode prior to air being purged from the pumps may cause damage to the pumps and cause the system to energize the heater to go into overheat condition.

Pump 1 (low-speed) is responsible for heating and filtration and will be referred to simply as the pump. Low speed pump will run every 30 minutes for 2 to 5 minutes to check the tubs water.

Setting Temperature

The last measured water temperature is constantly displayed.

To change the set temperature, press the “Warm” and “Cool” buttons. Pressing “Warm” or “Cool” will cause the temperature to flash. When the LCD stops flashing, the spa will heat to the new set temperature when required.

Setting Time

Setting the time-of-day is important for determining filtration times.

Press the “Menu” button until [TIME/SET] appears on the screen. Use the “Warm” and “Cool” buttons to adjust the hours. Press “Menu” to complete and move to minutes (15-minute increments). Use the “Warm” and “Cool” buttons to adjust the minutes. Press “Menu” to complete.



Filter Cycle

Nordic recommends two filter cycles daily for a total of four hours of filtration per day.

Best Practices: One filter schedule in the morning before morning usage and one filter cycle after nightly usage.

Press “Menu” until [FLTR] appears on the screen. F12 should be displayed on the right side of the screen. This indicates there will be 2 filter cycles within 24-hours.

Use the “Warm” and “Cool” buttons to adjust the hours of duration of the filter cycle. Press “Menu” to complete and move to minutes. Use the “Warm” and “Cool” buttons to adjust the minutes (15-minute increments) and press “MENU” to complete.

Press “Menu” to go back to the main screen.

If F12 is not displayed – please contact your local Nordic Hot Tubs Authorized Dealer.